



China model range

50 Hz range

Model name	Standby rating		Prime rating		Engine model	Standard alternator	Standard controller	Emission	Certification	Sound enclosure
	kVA	kWe	kVA	kWe						
C55D5	55	44	50	40	4BTA3.9-G2	UCI224D1	PC 1.1	UR	NA	No
C80D5	80	64	73	58	6BT5.9-G1	UCI224F1	PC 1.1	UR	NA	No
C90D5	90	72	82	65	6BT5.9-G1	UCI224G1	PC 1.1	UR	NA	No
C100D5	100	80	91	73	6BT5.9-G1	UCI274C1	PC 1.1	UR	NA	No
C110D5	110	88	100	80	6BTA5.9-G2	UCI274C1	PC 1.1	UR	NA	No
C150D5B	150	120	138	110	6BTAA5.9-G15	UCI274E1	PC 1.2	UR	NA	Yes
C175D5B	175	140	159	127	6BTAA5.9-G15	UCI274F1	PC 1.2	UR	NA	Yes
C200D5	200	160	181	145	6CTA8.3-G2	UCI274H1	PC 1.1	UR	NA	Yes
C220D5	220	176	200	160	6CTAA8.3-G7	UCI274H1	PC 1.2	UR	NA	Yes
C250D5	250	200	227	182	6CTAA8.3-G9	UCDI274J1	PC 1.2	UR	NA	Yes
C275D5B	275	220	250	200	6LTAA9.5-G3	UCDI274K1	PC 1.2	UR	NA	Yes
C300D5B	300	240	275	220	6LTAA9.5-G3	S4L1D-D41	PC 1.2	UR	NA	Yes
C330D5B	330	264	300	240	6LTAA9.5-G1	S4L1D-D41	PC 1.2	UR	NA	Yes
C350D5B	350	280	320	256	6LTAA9.5-G1	S4L1D-E41	PC 1.2	UR	NA	Yes
C400D5	400	320	360	288	QSG12-G3	S4L1D-F41	PC 2.2	UR	CE, UKCA, AS3000	Yes
C400D5EB	400	320	364	291	QSZ13-G7	S5L1D-C41	PC 2.2	EPA T3, EU IIIA, CSIII	CE, UKCA, AS3000	Yes
C450D5	450	360	410	328	QSG12-G4	S4L1D-G41	PC 2.2	UR	CE, UKCA, AS3000	Yes
C450D5EB	450	360	409	327	QSZ13-G7	S5L1D-C41	PC 2.2	EPA T3, EU IIIA, CSIII	CE, UKCA, AS3000	Yes
C500D5	500	400	455	364	QSZ13-G5	S5L1D-D41	PC 2.2	UR	CE, UKCA, AS3000	Yes
C550D5	550	440	500	400	QSZ13-G10	S5L1D-D41	PC 2.2	UR	CE, UKCA, AS3000	Yes
C550D5E	550	440	500	400	QSX15-G8	S5L1D-D41	PC 2.2	EU IIIA	CE, UKCA, AS3000	Yes

* Specifications may change without notice.

All ratings include radiator fan losses.

DCC available at standby power subject to Cummins' site-specific assessment. Please contact your Cummins Distributor.

CHINA MODEL RANGE

Model name	Standby rating		Prime rating		Engine model	Standard alternator	Standard controller	Emission	Certification	Sound enclosure
	kVA	kWe	kVA	kWe						
C640D5	640	512	582	466	KTAA19-G6	S5L1D-E41	PC 1.2	UR	CE, UKCA, AS3000	No
C700D5	706	565	640	512	VTA28-G5	S5L1D-F41	PC 1.2	UR	NA	No
C825D5	825	660	750	600	VTA28-G6	S6L1D-C41	PC 1.2	UR	NA	No
C900D5	900	720	820	656	QSK23-G3	S6L1D-D41	PC 3.3	UR	NA	No
C1000D5	1062	850	1012	810	KTA38-G5 / KTA38-G14	S6L1D-E41	PC 3.3	UR	NA	No
C1100D5B	1132	906	1029	823	KTA38-G5 / KTA38-G14	S6L1D-F41	PC 3.3	UR	NA	No
C1250D5A	1250	1000	1125	900	KTA38-G9	S6L1D-G41	PC 3.3	UR	CE, UKCA	No
C1250D2R	1400	1120	1258	1006	KTA50-G3	S7L1D-C41	PC3.3	UR	CE, UKCA, AS3000	Yes
C1400D5	1400	1120	1250	1000	KTA50-G3	S6L1D-H41	PC3.3	UR	NA	No
C1675D5A	1675	1340	1500	1200	KTA50-GS8	S7L1D-D41	PC3.3	UR	NA	No
C1875D5E	1875	1500	1700	1360	QSK50-G15	S7L1D-F41	PC3.3	Tier 2, CSIII	CE, UKCA, AS3000	No
C2000D5	2000	1650	1875	1500	QSK60-G3	S7L1D-G41 / S9H1D-A41	PC3.3	UR	CE, UKCA, AS3000	Yes
C2000D5EB	2000	1600	1875	1500	QSK50-G16	S7L1D-G41	PC3.3	Tier 2, CSIII	CE, UKCA, AS3000	No
C2000D5-PB	2063	1650	1875	1501	QSK60-G3	S7L1D-G41 / S9H1D-A41	PC3.3	UR	CE, UKCA, AS3000	Yes
C2250D5	2250	1800	2000	1600	QSK60-G4	S7L1D-H41 / S9H1D-B41	PC3.3	UR	CE, UKCA, AS3000	Yes
C2250D5E	2250	1800	2000	1600	QSK50-G17	S7L1D-H41 / S9H1D-B41	PC3.3	Tier 2, CSIII	CE, UKCA, AS3000	No
C2250D5-PB	2250	1800	2000	1600	QSK60-G4	S7L1D-H41 / S9H1D-B41	PC3.3	UR	CE, UKCA, AS3000	Yes
C2500D5A	2500	2000	2250	1800	QSK60-G8	S7L1D-J41 / S9H1D-C41	PC3.3	UR	CE, UKCA, AS3000	Yes
C2500D5A-PB	2500	2000	2250	1800	QSK60-G8	S7L1D-J41 / S9H1D-C41	PC3.3	UR	CE, UKCA, AS3000	Yes
C2750D5BE	2750	2200	2500	2000	QSK60-G23	S7L1D-K41 / S9H1D-D41	PC3.3	Tier 2, CSIII	CE, UKCA, AS3000	Yes
C2750D5BE-PB	2750	2200	2500	2000	QSK60-G23	S7L1D-K41 / S9H1D-D41	PC3.3	EPA Tier 2	CE, UKCA, AS3000	Yes
C3000D5BE	3000	2400	2750	2200	QSK78-G21	LVSI804W2 / S9H1D-D42	PC3.3	Tier 2, CSIII	CE, UKCA, AS3000	No

* Specifications may change without notice.

All ratings include radiator fan losses.

DCC available at standby power subject to Cummins' site-specific assessment. Please contact your Cummins Distributor.