



International model range

50 Hz range

Model name	Standby rating		Prime rating		DCC rating		Engine model	Standard alternator	Standard controller	Emissions certification	Sound enclosure
	kVA	kWe	kVA	kWe	kVA	kWe					
C17D5	16.5	13	15	12			X2.5-G2	SOL1-P1	PS0600		Yes
C22D5	18	17	20	16			X2.5-G2	SOL2-G1	PS0600		Yes
C28D5	27.5	22	25	20			X2.5-G2	SOL2-M1	PS0600		Yes
C33D5	33	26	30	24			X3.3-G1	SOL2-P1	PS0600		Yes
C38D5	38	30	35	28			X3.3-G1	S1L2J1	PS0600		Yes
C44D5L	44	35	40	32			4BTAA3.3-G14	UCI224C	PS0600	UR	Yes
C44D5I	44	35	40	32			4BTAA3.3-G13	UCI224C	PS0600	UR	No
C44D5E	44	35	40	32			B3.3-G14	UCI224C	PS0600	EU Stage IIIA	Yes
C55D5L	55	44	50	40			4BTAA3.3-G13	UCI224C	PS0600	UR	Yes
C55D5I	55	44	50	40			4BTAA3.3-G13		PS0600	UR	
C55D5E	55	44	50	40			B3.3-G14	UCI224 D	PS0600	EU Stage IIIA	Yes
C66D5L	66	53	60	48			4BTAA3.3-G13	UCI224F	PS0600	UR	Yes
C66D5I	66	53	60	48			4BTAA3.3-G13			UR	
C66D5E	66	53	60	48			B3.3-G14	UCI224F	PS0600		Yes
C90D5	90	72	82	65			6BTA5.9-G5	UCI224G	PC 1.2	UR	Yes
C90D5I	90	72	82	65			6BTA5.9-G5			UR	
C110D5	110	88	100	80			6BTA5.9-G5	UCI274C	PC 1.2	UR	Yes
C110D5I	110	88	100	80			6BTA5.9-G5			UR	
C150D5	150	120	136	109			6BTAA5.9-G6	UCI274E	PC 1.2	UR	Yes
C150D5I	150	120	136	109			6BTAA5.9-G6			UR	
C170D5	170	136	155	124			6BTAA5.9-G7	UCI274F	PC 1.2	UR	Yes
C170D5I	170	136	155	124			6BTAA5.9-G7			UR	
C175D5E	175	140	160	128			QSB7-G5	UCI274F	PC 1.2	EU Stage IIIA	Yes
C175D5I	175	140	160	128			QSB7-G18			UR	Yes
C200D5E	200	160	182	146			QSB7-G5	UCI274H	PC 1.2	EU Stage IIIA	Yes
C200D5I	200	160	182	146			QSB7-G18			UR	Yes

* Specifications may change without notice.

All ratings include radiator fan losses.

DCC available at standby power subject to Cummins' site-specific assessment. Please contact your Cummins Distributor.

INTERNATIONAL 50 Hz RANGE

Model name	Standby rating		Prime rating		DCC rating		Engine model	Standard alternator	Standard controller	Emissions certification	Sound enclosure
	kVA	kWe	kVA	kWe	kVA	kWe					
C220D5	220	176	200	160			6CTAA8.3-G7	UCI274H	PC 1.2	UR	Yes
C220D5E	220	176	200	160			QSB7-G5	UCI274H	PC 1.2	EU Stage IIIA	Yes
C220D5I	220	176	200	160			QSB7-G18			UR	Yes
C250D5	250	200	227	182			6CTAA8.3-G9	UCDI274J	PC 1.2	UR	Yes
C250D5E	250	200	230	184			QSL9-G7	UCDI274K	PC 1.2	EU Stage IIIA	Yes
C250D5I	250	200	227	182			QSB7-G19			UR	Yes
C275D5	275	220	250	200			QSL9-G5	UCDI274K	PC 1.2	UR	Yes
C275D5E	275	220	250	200			QSL9-G7	HC4D	PC 1.2	EU Stage IIIA	Yes
C275D5B	275	220	250	200			6LTAA9.5-G3	UCDI274K	PC 1.2	UR	Yes
C275D5I	275	220	250	200			6LTAA8.9-G4			UR	
C300D5B	300	240	275	220			6LTAA9.5-G3	HC4D	PC 1.2	UR	Yes
C300D5	300	240	275	220			QSL9-G5	HC4D	PC 1.2	UR	Yes
C300D5E	300	240	275	220			QSL9-G7	HC4D	PC 1.2	EU Stage IIIA	Yes
C300D5I	300	240	270	216			QSL9-G5			UR	
C330D5	330	264	300	240			QSL9-G5	HC4D	PC 1.2	UR	Yes
C330D5E	330	264	300	240			QSL9-G7	HC4D	PC 1.2	EU Stage IIIA	Yes
C330D5B	330	264	300	240			6LTAA9.5-G1	HC4D	PC 1.2	UR	Yes
C330D5I	330	264	300	240			QSL9-G5	HC4E	PS0602	UR	
C350D5B	350	280	320	256			6LTAA9.5-G1	HC4S	PC 1.2	UR	Yes
C400D5	400	320	360	288			QSG12-G1	HC4F	PC 2.2	UR	Yes
C400D5EB	400	320	360	288			QSZ13-G7	HC5C	PC 2.2	EU Stage IIIA	Yes
C450D5	450	360	409	327			QSG12-G1	HC5C	PC 2.2	UR	Yes
C450D5EB	450	360	409	327			QSZ13-G7	HC5C	PC 2.2	EU Stage IIIA	Yes
C500D5E	500	400	455	364	455	364	QSX15-G8	HC5C	PC 2.2	UR	Yes
C500D5	500	400	455	364			QSZ13-G5	S5L1D-D41	PC 2.2	EU Stage II	Yes
C550D5E	550	440	500	400	500	400	QSX15-G8	HC5D	PC 2.2	UR	Yes
C550D5	550	440	500	400			QSZ13-G10	S5L1D-D41	PC 2.2		Yes
C640D5	640	512	582	466			KTA19-G6	HC5E	PC 1.1	UR	No
C700D5	706	565	640	512	640	512	VTA28-G5	HC5F	PC 3.3	UR	No
C825D5	825	660	750	600	750	600	QSK23-G3	S6L1C4	PC 3.3	UR	Yes
C825D5E	825	660	750	600	750	600	QSK23-G9	S6L1C4	PC 3.3	EPA Tier 2	Yes

* Specifications may change without notice.

All ratings include radiator fan losses.

DCC available at standby power subject to Cummins' site-specific assessment. Please contact your Cummins Distributor.

INTERNATIONAL 50 Hz RANGE

Model name	Standby rating		Prime rating		DCC rating		Engine model	Standard alternator	Standard controller	Emissions certification	Sound enclosure
	kVA	kWe	kVA	kWe	kVA	kWe					
C825D5A	825	660	750	600	750	600	VTA28-G6	S6L1C4	PC 3.3	UR	No
C900D5	900	720	820	656	820	656	QSK23-G3	S6L1D4	PC 3.3	UR	Yes
C900D5E	900	720	820	656	820	656	QSK23-G9	S6L1D4	PC 3.3	EPA Tier 2	Yes
C1000D5B	1000	800	900	720	900	720	KTA38-G14	S6L1DE4	PC 3.3	UR	Yes
C1000D5	1041	833	939	751	939	751	QST30-G3	S6LIDD4**	PC 3.3	UR	No
C1100D5	1110	888	1000	800	1000	800	QST30-G4	S6LIDD4	PC 3.3	UR	No
C1100D5B	1132	906	1029	823	1029	823	KTA38-G14	S6L1DF4	PC 3.3	UR	Yes
C1250D5A	1250	1000	1125	900			KTA38-G9	PI734A	PC 3.3	UR	No
C1250D5AB	1250	1000	1125	900			KTA38-G9	S6L1DG41	PC 3.3	UR	Yes
C1400D5	1400	1120	1250	1000	1250	1000	KTA50-G3	PI734B	PC 3.3	UR	No
DQGAN	1400	1120	1275	1020	1275	1020	QSK50-G4	PI734B	PC 3.3	UR	No
C1675D5A	1675	1340	1500	1200	1500	1200	KTA50-GS8	PI734D	PC 3.3	UR	No
DQGAG	1700	1269	1540	1232	1540	1232	QSK50-G4	PI734D	PC 3.3	UR	No
C1760D5E	1760	1408	1600	1280	1600	1280	QSK60-GS3	PI734D	PC 3.3	UR	No
C1760D5	1760	1408	1600	1280	1600	1280	KTA50-G23	S7L1D-E4	PC 3.3	UR	No
C1760D5	1760	1408	1600	1280	1600	1280	KTA50-G23			UR	
DQGAM	1825	1460	1650	1320	1650	1320	QSK50-G7	PI734F	PC 3.3	EPA Tier 2	No
C1875D5	1875	1500	1700	1360	1700	1360	KTA50-G23	S7L1D-F4	PC 3.3	UR	No
C1875D5E	1875	1500	1700	1360			QSK50-G15	S7L1D-F4		EPA Tier 2	
C2000D5B	2000	1600	1800	1440	1800	1440	KTA50-G23	S7L1D-G4	PC 3.3	UR	No
C2000D5E	2000	1600	1825	1460	1825	1460	QSK60-GS3	PI734F	PC 3.3	UR	No
DQKAH	2000	1650	1825	1460	1825	1460	QSK60-G11	PI734F	PC 3.3	EPA Tier 2	No
C2000D5EB	2000	1600	1875	1500	1875	1500	QSK50-G16	S7L1D-G4	PC 3.3	EPA Tier 2	
C2000D5	2063	1650	1875	1500	1875	1500	QSK60-G3	PI734F	PC 3.3		
C2250D5	2250	1800	2000	1600	2000	1600	QSK60-G4	PI734G	PC 3.3	UR	No
DQKAG	2250	1800	2000	1600	2000	1600	QSK60-G11	PI734F	PC 3.3	EPA Tier 2	No
C2250D5E	2250	1800	2000	1600			QSK50-G17			EPA Tier 2	
C2500D5A	2500	2000	2250	1800	2250	1800	QSK60-G8	LVS1804R	PC 3.3	UR	No
DQKAJ	2500	2000	2000	1600	2250	1800	QSK60-G18	LVS1804S	PC 3.3	EPA Tier 2	No
C2750D5BE	2750	2200	2500	2000	2500	2000	QSK60-G23	LVS1804W	PC 3.3	EPA Tier 2	No
C3000D5	3000	2400	2750	2200	2750	2200	QSK78-G9/G24	LVS1804S	PC 3.3	UR	No

* Specifications may change without notice.

All ratings include radiator fan losses.

DCC available at standby power subject to Cummins' site-specific assessment. Please contact your Cummins Distributor.

INTERNATIONAL 50 Hz RANGE

Model name	Standby rating		Prime rating		DCC rating		Engine model	Standard alternator	Standard controller	Emissions certification	Sound enclosure
	kVA	kWe	kVA	kWe	kVA	kWe					
C3000D5E	3000	2400	2750	2200	2750	2200	QSK78-G23/G16	LVS1804S	PC 3.3	EPA Tier 2	No
C3500D5	3500	2800	3125	2500	3125	2500	QSK95-G4	LVS1804W	PC 3.3	UR	No
C3500D5E	3500	2800	3125	2500	3125	2500	QSK95-G5/G10	LVS1804W	PC 3.3	EPA Tier 2	No
C3750D5	3750	3000	3350	2680	3350	2680	QSK95-G4	LVS1804X	PC 3.3	UR	No
C3750D5E	3750	3000	3350	2680	3350	2680	QSK95-G10	LVS1804X	PC 3.3	EPA Tier 2	No

* Specifications may change without notice.

All ratings include radiator fan losses.

DCC available at standby power subject to Cummins' site-specific assessment. Please contact your Cummins Distributor.



Cummins Inc.
Box 3005
Columbus, IN 47202-3005
U.S.A.

cummins.com

Bulletin 6614069 Produced in U.S.A. Rev. 8/25
©2025 Cummins Inc.