



For '98 1/2 and '99 Dodge Ram Trucks Equipped with the Cummins ISB5.9 Engine

Parts Manual

Application Notes

This Cummins E Brake by Jacobs has been specifically engineered for '98 and '99 Dodge Ram trucks equipped with the Cummins ISB5.9 Turbo Diesel engine. For all installations, order kit P/N 3800352. For installation on 1999 Trucks equipped with the ISB engine you must also order Attaching Parts Group, P/N 3800555.

Important!

For all 99 model year trucks, the ECM has been preprogrammed for E Brake operation. All 98 1/2 trucks must have an ECM Service Calibration performed by an authorized Cummins Service Center before the E Brake will operate. See your Cummins dealer for details.

For additional information or technical support, contact Cummins Customer Assistance Center by calling 1-800-DIESELS (1-800-343-7357)




THE EXHAUST BRAKE ASSEMBLY IS NOT FIELD SERVICEABLE. DO NOT ATTEMPT TO DISASSEMBLE E BRAKE COMPONENTS OR

DAMAGE TO THE E BRAKE MAY OCCUR.

NI = Not Illustrated NSS = Not Sold Separately

E Brake Assembly Group, P/N 3800356

III. No. P/N	Description	Qty./ Group	
1 3800354	E Brake assembly	1	
NI 3800627	Gasket	1	
NI 3945077	"V" clamp	1	



'99 Attaching Parts Group, P/N 3800555 Sold separately - not included in kit (required for '99 model year trucks only)

III. No. P/N	Description	Qty./ Group
NI 3527759	Turbo Outlet Adapter	1
NI 3535001	Gasket	1
NI 3530556	Capscrew	5

Wire Harness Group, P/N 3870864

III.		Qty./
No. P/N	Description	Group
1 NSS	Wire Harness	1
NI NSS	O-Ring	1




Dash Switch Group, P/N 3800359

111.			Qty./
No	. P/N	Description	Group
NI	NSS	Dash switch/harness assy.	1
NI	NSS	Connector Housing	1
NI	NSS	Terminal	1
NI	NSS	Conduit, 16 1/2" long	1

Pneumatic Group, P/N 3800358

III. No.	. P/N	Description	Qty./ Group
1	3933133	Vacuum solenoid assembly	1
2	NSS	Hose Barb Fitting	
		(1/4" hose to 1/4" NPT)	1
3	NSS	90° elbow	
		(1/4" hose to 1/4" NPT)	1
	3800454	Bracket Group	
4	NSS	Mounting plate	1
5	NSS	Isolator grommets	4
6	NSS	Fender washer	4
7	NSS	Lock washer, M6	4
8	NSS	Hex bolt, $M6 \times 1 \times 40$	4
NI	NSS	Well nut	4
NI	NSS	Machine screw, #8-32 x 3	3/8"2
NI	NSS	Lock washer, #8	2
NI	NSS	Hose, 1/4" I.D. x 6"	2
Ni	NSS	Hose, 1/4" I.D. x 30"	2
NI	NSS	Hose, 1/4" I.D. x 1.5"	1
NI	NSS	"Y" connector,	1
		$(1/4" \times 1/4" \times 1/4")$	
NI	NSS	Hose clamps	1
NI	NSS	Lock nut, M6 x 1	1
9	NSS	P-clip	1
NI	NSS	Cable ties	12





E BRACE by Jacobs



Cummins Engine Company, Inc. Box 3005 Columbus, IN 47202-3005 U.S.A.

Bulletin 3401741 Printed in U.S.A. 6/98 ©1998 Cummins Engine Company, Inc. and Jacobs Vehicle Systems, Inc.